
DINGLI Exceed New Height


GTBZ16SU Telescopic Boom Lifts

SPECIFICATIONS

| Size | Metric | British |
|---|-------------|---------------|
| Max. Working Height | 15.60m | 51ft 2in |
| Max. Platform Height | 13.60m | 44ft 7in |
| Max. Front Outreach(Outriggers Extension) | 8.46m | 27ft 9in |
| Max. Rear Outreach(Outriggers Extension) | 4.66m | 15ft 4in |
| Max. Platform Slide | 1.51m | 4ft 11in |
| Overall Length 🚯 | 7.35m | 24ft 1in |
| Overall Width(Stowed) | 2.50m | 8ft 2in |
| Overall Width(Transport) | 2.31m | 7ft 7in |
| Overall Height(Rails Up) 🖸 | 3.55m | 11ft 8in |
| Overall Height(Rails Down) | 2.62m | 8ft 7in |
| Overall Height(Transport) | 2.37m | 7ft 9in |
| Platform Size(Length \mathbf{O} ×Width \mathbf{G}) | 6.70m×2.24m | 22ft× 7ft 4in |
| Ground Clearance | 0.32m | 1ft 1in |
| Wheelbase | 3.80m | 12ft 6in |
| Turning Radius(Inside/Outside) | 2.45m/5.50m | 8ft/18ft 1in |
| Tyres | 355-55/D625 | 355-55/D625 |

ENGINE





Performance

| S.W.L | 1800kg | 3968lb |
|----------------------|-----------|-----------|
| Max. Goods Loading | 1350kg | 2976lb |
| Max. Occupants | 4 | 4 |
| Platform Swing Angle | +/-90° | +/-90° |
| Gradeability | 40% | 40% |
| Travel Speed(Stowed) | 6.0km/h | 3.73mph |
| Travel Speed(Raised) | 0.9km/h | 0.56mph |
| Max.Working Slope | X-3°/Y-5° | X-3°/Y-5° |
| Chassis Leveling | 10° | 10° |

| Weight |
|--------|
| |

Overall Weight

| Power | | | |
|-----------|------------|----------------------|-------------------------|
| Diesel En | gine | Deutz TD2.9 L4/55.4k | W Deutz TD2.9 L4/55.4kW |
| Hydraulio | : Oil Tank | 216L | 57gal |

13350kg

29431lb





FEATURES

Standard Items

- Proportional Controls
- Manual Safety Pump
- Hour Meter
- Tilt Sensor
- 180° Platform Rotation

Slide Platform

- Self-leveling Platform
- Anti-restart Engine Protection
- The Glow Plugs For Cold Starting

Chassis Auto-leveling

Oscillating Axle

- Automatic Outriggers
- European III Emission Engine
- Foam-filled Tyres
- Four-Wheel Steering
- Four-Wheel Drive
- Onboard Diagnostic System
- All Motion Alarm
- Horn
- Flashing Beacon
- Hydraulic Oil Cooler



DINGLI AWP INDIA PRIVATE LIMITED

Address: Sahney Towers, 81, First Floor, Poonamallee High Road, Nerkundram,

Chennai, Tamil Nadu - 600 107

Telephone: +91-98846 48464

E-mail: support@dinglisaarc.com

Website: https://dinglisaarc.com



Due to continuous technology updates, technical parameters are subject to change without notice. This picture book is for reference only, the actual product shall prevail. The copyright is owned by zhejiang dingli, any content may not be copied for any purpose without written permission. 2022-09